



SAFETY DATA SHEET

MER LONG LIFE TYRE DRESSING (NEW FORMULA)

Page 1

Issued: 01/10/2009

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MER LONG LIFE TYRE DRESSING (NEW FORMULA)
Product code: VPT
Company name: Farecla Products Limited
Broadmeads
Ware
Hertfordshire
SG12 9HS
UK
Tel: +44 (0)1920 465041
Fax: +44(0)1920 466557
Emergency tel: +44(0)1920 465041 (office hours only)
Email: technical@farecla.com

2. HAZARDS IDENTIFICATION

Main hazards: Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: NAPHTHA (PETROLEUM) HYDRODESULPHURISED LIGHT, DE-AROMATISED
70-90%
EINECS: 295-434-2 CAS: 92045-53-9
[Xi] R38; [N] R51/53; [Xn] R65; [F] R11; [-] R67

- NAPHTHA (PETROLEUM) HDRODESULPHURISED HEAVY <1%
EINECS: 265-185-4 CAS: 64742-82-1
[-] R10; [N] R51/53; [Xn] R65; [-] R66; [-] R67

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

[cont...]

SAFETY DATA SHEET
 MER LONG LIFE TYRE DRESSING (NEW FORMULA)

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.
 Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: NAPHTHA (PETROLEUM) HYDRODESULPHURISED LIGHT, DE-AROMATISED
 EU - 8 hour TWA: 1400mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Pleasant

SAFETY DATA SHEET

MER LONG LIFE TYRE DRESSING (NEW FORMULA)

Evaporation rate: Fast
Solubility in water: Insoluble
Viscosity: Non-viscous
Flash point°C: 38
Relative density: 0.747

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.
Conditions to avoid: Heat.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to skin. May cause lung damage if swallowed.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Not biodegradable.
Bioaccumulative potential: Bioaccumulation potential.
Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.
PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.
NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1993	ADR Class: 3
Packing group: II	Classification code: F1
Shipping name: FLAMMABLE LIQUID, N.O.S.	
Labelling: 3	Hazard ID no: 33

SAFETY DATA SHEET
 MER LONG LIFE TYRE DRESSING (NEW FORMULA)



IMDG / IMO

UN no: 1993	Class: 3
Packing group: II	EmS: F-E,S-E*
Marine pollutant: .	Labelling: 3

IATA / ICAO

UN no: 1993	Class: 3
Packing group: II	Packing instructions: 305(P&CA); 307(CAO)
Labelling: 3	

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.
 Harmful.



Risk phrases: R10: Flammable.
 R38: Irritating to skin.
 R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65: Harmful: may cause lung damage if swallowed.
 R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.
 S29: Do not empty into drains.
 S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
 S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Haz. ingredients (label): NAPHTHA (PETROLEUM) HYDRODESULPHURISED LIGHT, DE-AROMATISED

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R11: Highly flammable.
R67: Vapours may cause drowsiness and dizziness.
R10: Flammable.
R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.